

IC-i2a-Px12W-AC

The IC-i2a-Px12W-AC is a compact in ceiling full function 2 Megapixel PTZ. This Utility PTZ is ideal for professional retail/FMCG applications where discrete fully functional HD cameras are required

The IC-i2a-Px12W-AC has a 1/3" Sony Exmor Sensor that delivers 2 Megapixel resolution and coupled with the Ambarella chipset delivers bandwidth friendly HD performance. The unit also incorporates a powerful 12x optical zoom lens and many other features normally associated with larger, more expensive PTZ's.



Main Features

- 1/3" Exmor CMOS
- Ambarella Chipset
- 2 Megapixel
- In-Ceiling Mount Design
- H.264 & MJPEG Video Compression
- 1080P/720P/D1 @ 25/30FPS
- 12x Optical Zoom (5.1 mm-61.2mm)
- Lens Angle = 51.3° - 4.64°
- Onvif (Ver 2) Profile S Compliant
- ICR true Day/Night
- Min Illumination: Colour: 0.05 Lux/F1.6, B/W: 0.005Lux/F1.6
- BLC / HLC / DWDR
- 2D / 3D Noise Reduction
- 360° Endless Pan
- 255 Pre-sets, 5 Pattern, 8 Tour, 5 Auto Scan, Auto Pan
- Power up Action, Idle Motion, Time Tasks
- Auto Recognise ICR-SD, Pelco D, Pelco D Protocols
- Up to 20 Users Network Access
- RJ-45 (10/100Base-T) Network Port
- Network Features: IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
- FREE SmartICRSS Client Software for Windows and Mac OS X
- ICRSS Pro Application for iOS (iPhone / iPad), Android (Smart Phone and Tablets) & Windows Phone
- 1 channel in/out Audio Interface
- Micro SD Slot (Max 64GB)
- 2 Alarm Input / 1 Alarm Output
- Active X and Quick Time Web Browser
- AC24V/1.5A (±10%) / <12W
- POE+(802.3at)
- Dimensions: Φ198mm×158mm
- Weight: 2.3KG



www.icrealtime.net

European Head Office

IC Realtime,
12 Knockmitten Lane,
Western Industrial Estate,
Dublin 12, Ireland.
Phone 0818 903 365
(ROI National call rate)
Phone +353 (0) 1 4268275
Fax +353 (0) 1 4196245
Email info@icrealtime.ie

UK Office

IC Realtime UK
Surrey Technology Centre,
40 Occam Road,
Guildford GU2 7YG,
United Kingdom
Phone +44 (0) 1483 685460
Fax +44 (0) 1483 685461
Email sales@icrealtime.co.uk

USA Head Office

IC Realtime, LLC,
3050 N Andrews Ave EXT,
Pompano Beach, FL 33064, USA
Phone (954) 772-5327
Toll (866) 997 9009
Fax (866) 860-3860
Email info@icrealtime.com

USA West Coast Office

IC Realtime West Coast,
14180 W Van Buren Street,
Suite B-105, Goodyear,
AZ 85338, USA
Phone (602) 910 3432
Fax (602) 626 3545
Email info@icrealtime.com

Model	IC-i2a-Px12W-AC
VIDEO	
Image Sensor	1/3" Exmor CMOS
Chipset	Ambarella
Resolution	2 MegaPixel
Effective Pixels	1944(H) x 1092(V)
Scanning System	Progressive
Electronic Shutter Speed	1/3s - 1/30,000s
Min. Illumination	Colour: 0.05 Lux/F1.6, B/W: 0.005Lux/F1.6
S/N Ratio	>55dB
ENCODE	
Compression	H.264/ MJPEG
Resolution	1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480)/CIF(352×288/352×240)
FPS - Main Stream	1080P/D1 (1 - 25/30fps) /720P(1-50/60fps)
FPS - Sub Stream	D1/CIF(1 - 25/30fps)
Bit Rate	H.264: 448K - 8192Kbps, MJPEG: 56K - 20480Kbps
FEATURES	
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR (Digital WDR)
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Gain Control	Auto/Manual
Noise Reduction	2D / 3D
Privacy Masking	Up to 24 areas
Digital Zoom	16x
LENS	
Focal Length	5.1 mm-61.2mm (12x Optical zoom)
Max Aperture	F1.2- F2.1
Focus Control	Manual
Angle of View	51.3° - 4.64°
Close Focus Distance	100mm-1000mm
PTZ FUNCTIONS	
Pan/Tilt Range	Pan: 0° - 360° endless; Tilt: -2° - 90°, auto flip 180°
Manual Control Speed	Pan: 0.1° - 300°/s; Tilt: 0.1° -120°/s
Preset Speed	Pan: 300°/s; Tilt:200°/s
Preset	80(ICR-SD) , 255(Pelco-P/D)
PTZ Mode	5 Pattern, 8 Tour, 5 Auto Scan, Auto Pan
Speed Setup	Human-oriented focal length/ speed adaptation
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/Pan/Scan/Tour/Pattern if there is no command in the specified period
Time Task Protocol	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time ICR-SD, Pelco-P/D (Auto recognition)
NETWORK	
Ethernet Port	RJ-45 (10/100Base-T)
Wi-Fi	N/A
Network Function	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF	ONVIF Profile S
Max Online Users	20
AUDIO	
Interface	1/1 channel In/Out
Compression	G.711a / G.711u (32kbps) / PCM (128kbps)
OTHER INTERFACES	
Memory Slot	Micro SD, Max 64GB
RS-485	N/A
Alarm	2/1 channel In/Out
GENERAL	
Power Supply	AC24V/1.5A (±10%), POE+(802.3at)
Power Consumption	<12W
Working Environment	-10°C - 60°C / Less than 90% RH
IP Rating	N/A
Vandal Resistance	N/A
Dimensions	Φ198mm×158mm
Weight	2.3Kg